



For any type of door or window system, regardless of the material that constitutes its supporting structure, functionality and performance must satisfy the legal obligations or mandatory standards that demand already excellent levels.

For each construction system, be it Wood, Wood/Aluminium, PVC, Aluminium, it is possible to vary the energy, acoustic, sealing performance against the external climate, safety, functionality, etc. by varying the type of filling components and supporting and manoeuvring devices almost common transversally to every constructive system.

The load-bearing structure, which accounts for approximately 1/3 of the raw materials, makes a huge difference to the construction system that not only characterises the product, that is the window or door, but has a very strong ENVIRONMENTAL, SOCIAL, ECONOMIC, AESTHETIC, CULTURAL influence.

The purchase of an asset such as a window or door, for all the implications that this entails, therefore deserves considerations and reflections that today must necessarily go beyond mere economic and performance evaluation so that it becomes a responsible and informed purchase over time.

WOOD, TIMELESS BEAUTY AND REFINEMENT



CUSTOMISABLE



ECO-COMPATIBLE AND ECO-SUSTAINABLE



IT IS LIVING MATTER SCULPTED BY MAN



WORKING WITH WOOD IS ART



Characteristics



DESCRIPTION

Door frames with triple gasket, in laminated wood with 3 layers (frame) and 4 layers (door) in essence, choose between: pine, fir, oak, okoumè, larch or others on request



WOODEN PROTECTION

Surface treatment of wood with products based on acrylic resins in aqueous emulsion; the applied cycle varies from three to six coats depending on the finish and the required durability.



DIMENSIONS

Fixed lamellar frame nominal section 68 x 82 mm.
Mobile lamellar panel nominal section 87 x 79 mm.



HARDWARE

Maico Multi-Matic standard hardware with tilt and turn panel, lever rod and micro-ventilation. Complete with anti-burglary striker plates and pawls along the entire perimeter.



GASKET AND SEAL

Triple abutment sealing profile with triple gasket.
Shaped glazing bead of different shapes.



DOUBLE-GLAZING

Use of low-emission double-chamber triple glazing with Argon gas as standard, in accordance with the current regulations. Of variable thicknesses and types (solar control, safety, acoustic, satin...) according to requirements. Also available with warm edge ducts.



THERMAL TRANSMITTANCE*

Thermal insulation achievable up to UW value of 0.80 W/m²K

*calculated thermal values (according to the standard UNI EN ISO 10077-1 and 2) with fir wood thermal transmittance on 1 panel window dimensions 1230 x 1480mm (according to the standard UNI EN 14351-1), low-emission double glazing with value Ug = 1.1 (W/m²K)



ACOUSTIC PROTECTION

Starting from 31 dB for windows based on glass noise reduction values up to 45 dB.





INTERIOR



EXTERIOR



Strengths



FINISHES OF YOUR CHOICE

The 32 standard finishes of your choice, with the possibility of further customisation, are soft like leather, clear like the water they are made of, coloured as nature intended with which they are friends, in step with the trends.



STANDARD WARRANTY*



Functionality of the windows
- 10 YEARS



No fogging inside the glazing
- 10 YEARS



Non-lamination of the laminated profile of wooden and wooden/aluminium windows- 10 YEARS



PREMIUM*



Window functionality - 10 YEARS



Paint durability of long-life painted windows ral 9001, 9010, 9016, 1013 - 15 YEARS**



Paint durability of painted windows long life dark stained colours - 10 YEARS**



No fogging inside the double-glazing - 10 YEARS



Non-lamination of the laminated profile of wooden and wooden/aluminium windows- 10 YEARS

* See the conditions set out in the warranty certificate and the provisions of article 5 of the general terms and conditions of sale

** According to the values defined by the standards ISO 4628-2-4-5, UNI EN 13722, UNI 8941-1-2-3



DESIGN


Our windows have a highly topical aesthetic, reflecting a clear language of forms. The building systems in step with the times, linked to the attention to detail, are adaptable to any environment to meet the individuality and functionality needs of our customers.




Concealed hinge




Coplanar kit with concealed hinge



"Type 1" round Soft glazing bead



"Type 3" square glazing bead




"Type 4" baroque glazing bead



T1 overlap wire cover



T2 coplanar wire cover



Central node entry "0" A6



Symmetrical central node A9



Central asymmetrical node A5



SAVINGS


Waterproofing, profiles, glass with synthetic material spacer, gaskets and installation without a thermal bridge have a considerable influence on energy savings and, consequently, on the cost of bills.

Finishes


STRIP 1 - STANDARD




Essence: Pine
Colour: Natura




Essence: Pine
Colour: Ambra



Essence: Okoumè
Colour: Ambra




Essence: Oak
Colour: Ambra




Essence: Pine
Colour: Cannella




Essence: Okoumè
Colour: Cannella




Essence: Oak
Colour: Cannella




Essence: Pine
Colour: Miele



Essence: Okoumè
Colour: Miele




Essence: Oak
Colour: Miele




Essence: Pine
Colour: Brandy




Essence: Okoumè
Colour: Brandy




Essence: Oak
Colour: Brandy



Essence: Pine
Colour: Moro




Essence: Okoumè
Colour: Moro




Essence: Oak
Colour: Moro


STRIP 2 - WITH SURCHARGE




Essence: Pine
Colour: Corda




Essence: Okoumè
Colour: Corda




Essence: Oak
Colour: Corda




Essence: Pine
Colour: Fieno




Essence: Okoumè
Colour: Fieno




Essence: Oak
Colour: Fieno




Essence: Pine
Colour: Argilla




Essence: Okoumè
Colour: Argilla




Essence: Oak
Colour: Argilla



Essence: Pine
Colour: Vinaccia



Essence: Okoumè
Colour: Vinaccia




Essence: Oak
Colour: Vinaccia




Essence: Pine
Colour: Sbiancato cenere



Essence: Pine
Colour: Ral 9010



Essence: Okoumè
Colour: Ral 9001



Essence: Oak
Colour: Ral 1013

The colours are approximate
They may undergo variations

OTHER COLOURS ON REQUEST.



GIEMME
Italian Windows Design



For technical, constructive and typographical reasons, the colours, descriptions, technical and dimensional details, as well as any other indication and/or information contained in this catalogue may be changed without notice, also based on technological evolution or on the availability of certain materials and/or components. In order to avoid any misunderstanding with its customers, Giemme Forli srl invites you to view all the characteristics of its production at the authorised points of sale. VERS. 0V87 / 11-22-EN